



Application uses a Junction box instead of a Marshalling box

Symbol	Model Number	Description	Qty
	RMKS-DAL4-SZ	PowPak with DALI	1
	RMKS-CCO1-24-B	PowPak CCO Module	1
	LRF3-OCR2B-P-WH	Radio Powr Savr Wireless Ceiling Occupancy Sensor	2
	PK2-3BRL-TAW-L01	Pico Wireless Control On/Off and Raise/Lower	1
	LPFP-S1-TAW	Pico Wireless Faceplate (Single)	1

Control Strategies



Occupancy/Vacancy



High-end Trim/Tuning

Lighting Energy Savings*

60%

* Go to lutron.com/references for more information.

Lighting Functionality

Occupant Enters:

All lights automatically turn on to maximum light level. Maximum light level is set to 80%.

When Occupied:

Manual: Occupant uses wall dimmer to set desired light levels for all lights.

Occupant Exits:

All lights automatically shut off 15 minutes (by default) after all occupants exit.

Advanced Functionality:

The CCO PowPak triggers the solenoid for an automatic flush.

Add a Vive wireless hub to enable simple setup and rezoning, system monitoring, timeclock functionality, and advanced integration.

Visible System Components



Pico wireless control



Radio Powr Savr wireless ceiling-mount occupancy sensor

Type of Solution

Recommended Solutions: Have advanced functionality for greater comfort and energy savings.