

D3
DOWNLIGHT FAMILY

# The D3 Solution



# Natural Light

Natural Light changes in color and intensity throughout the day, like sunlight.



# **Tunability**

RGBW tunable-spectrum light enables wide, dynamic range of white light from 1400K to 10000K and dimming to 0.1%, producing high fidelity white, pastels, and saturated colors.



### Wireless

Ketra offers a flexible solution for a myriad of wire-free, wholeinstallation scenarios integrating light fixtures, sensors, and controls making it easy to control any space.



## Tech

Patented microchip and multi-color LED module within every light source provides accurate, perfectly calibrated light over the life of the product.




# Complete Solution

Ketra's D3 delivers a fully tunablespectrum of white, saturate, and pastel light for fixed, adjustable and wall-wash applications within a low-profile 3 ½" housing.


# D3 Downlight

Ketra's D3 family includes fixed, adjustable, and wall-wash downlights. Every model features low-profile housing, wireless communication, and field replaceable optics and electronics. With a wealth of trim and optic accessories, the D3 is ideal for a large variety of applications. It uses a fully-tunable spectrum capable of delivering high quality white, saturated, and pastel light.


**FIXED** 



**ADJUSTABLE** 



WALL WASH



FIELD ADJUSTABLE EMITTER HEIGHT



LOW PROFILE IC HOUSING Fixture height 3 ½"



FIELD REPLACEABLE OPTICS



WIRELESS CONTROL



15° HIGH OUTPUT 15° LOW GLARE 25° HIGH OUTPUT 25°LOW GLARE 40° HIGH OUTPUT 40° LOW GLARE 60° HIGH OUTPUT

WALL WASH

## DELIVERED LUMEN OUTPUT<sup>1</sup>

Flanged

High Output				Low Glare			
Beam Angle (Shallow)	9W	13W	18W	Beam Angle (Shallow)	9W	13W	18W
15°	682lm	928lm	1148lm	15°	650 lm	882lm	1092lm
25°	678lm	923lm	1142lm	25°	623lm	845lm	1046lm
40°	646lm	878lm	1087lm	40°	569lm	772lm	955lm
60°	630lm	857lm	1061lm	60°	561lm	760lm	941lm
					9W	13W	18W
Housins				Wall Wash	414lm	573lm	705lm



Mud-in

# ROUND SQUARE BEVEL PINHOLE PINHOLE

# TRIM COLOR OPTIONS





## BLACK

## WHITE

## TRIM ACCESSORY OPTIONS

- SOLITE LENS
- FROST LENS

Downlight is wet location rated when trim is installed with lens; damp location rated otherwise

## OPTIC ACCESSORY OPTIONS


- · SOLITE ACCESSORY
- FROST ACCESSORY
- HEX LOUVER


 $<sup>^1</sup>$  All performance measurements taken with 1" trim, with light engine at nadir at the low regress position, at 3000K, 25°C ambient, 100% power input, unless otherwise stated.

# Complete Wiring Solutions


Ketra's D3 Downlight can easily be integrated with a variety of lighting and control situations.


0-10 Low Voltage Dimmer Control






Occupancy and Photocell Control to Ketra N3







Have questions? Email sales@ketra.com, or call 512.347.1100 x2.

